## **ASSIGNED**

## AMENDED

No. 60072

## APPLICATION FOR PERMIT TO APPROPRIATE THE PUBLIC WATERS OF THE STATE OF NEVADA

Date	of filing in State Engineer's Office
Retu	rned to applicant for correction. JUL 2 8 1994
Cor	rected application filed
Мар	filed <b>AUG 1 5 1994</b>
	The applicant Major Barite Inc John H. Uhalde, Agent
*******	1975 Palisade Drive , of Reno Street and No. or P.O. Box No. City or Town
	Nevada 89509, hereby makes application for permission to appropriate the public State and Zip Code No.
wate	ers of the State of Nevada, as hereinafter stated. (If applicant is a corporation, give date and place of incorporation; if a
copa	ortnership or association, give names of members.)
1.	The source of the proposed appropriation is underground  Name of stream, lake, spring, underground or other source
2.	The amount of water applied for is 1.5 C.F.S. second-feet  One second-foot equals 448.83 gals. per min.
	(a) If stored in reservoir give number of acre-feet
3.	The water to be used for mining, milling, dust control & domestic  Irrigation, power, mining, manufacturing, domestic, or other use. Must limit to one use.
4.	If use is for:
	(a) Irrigation, state number of acres to be irrigated
	(b) Stockwater, state number and kinds of animals to be watered.
	(c) Other use (describe fully under No. 12. "Remarks"
	(d) Power:
	(1) Horsepower developed
_	(2) Point of return of water to stream
	The water is to be diverted from its source at the following point. Lot 1 (NE½NE½) of Section 24, T.29N  Describe as being within a 40-acre subdivision of public
	R.47E., M.D.B.&M. or at at point from which the NE corner of said Section 24 survey, and by course and distance to a section corner. If on unsurveyed land, it should be so stated.
	bears N. 40°55'49" E., for a distance of 895.70 feet.
6.	Place of use. All of Section 9, N <sup>1</sup> / <sub>2</sub> and the SE <sup>1</sup> / <sub>4</sub> of Section 10, E <sup>1</sup> / <sub>2</sub> of Section 15,  Describe by legal subdivision. If on unsurveyed land, it should be so stated.
,	$S_{\frac{1}{2}}$ of Section 14 and the $N_{\frac{1}{2}}$ of Section 24; All in T.29N., R.47E., M.D.B.&M.
7. 1	Use will begin about Jan. 1 and end about Dec. 31 of each year.  Month and Day Month and Day
	Description of proposed works. (Under the provisions of NRS 535.010 you may be required to submit plans and
	specifications of your diversion or storage works.) drilled well, pump & mill for processing
	State manner in which water is to be diverted, i.e. diversion structure, ditches and
ī	himes drilled well with nump and mater, are

11. Estim	ated time requ	ired to complete the	e application	of water to beneficial use	2 years	•••••
	arks: For use amptive use:	other than irrigatio	on or stock wa	atering, state number and	type of units to be serve	ed or annual
*********	For dust	control of the	e roads, e	atc. within the pla	ce of use as desc	ribed
	under #6	it is estimate	ed the amo	ount of water used	daily will be 20,	000
	gallons.	It is estimat	ted water	will be used 120 d	ays per year. He	nce
	annual co	nsumption will	l be 2,400	0,000 gallons.		
		-		Bys/Charles C. A	rmuth, Jr. rmuth, JrSurvey	
Compared	ı ir/ iv	dl/cms		Charles C. A 1262 Hannah		or
				Elko, NV. 89		
Protested.						
		<b>A</b>	 APPROVAL	OF STATE ENGINEE	<b>.</b>	
	is to certify th limitations and		d the foregoin	ng application, and do he	ereby grant the same, su	abject to the
Ü			ssued s	ubject to exis	sting rights.	It i:
	rstood th	at the amou	int of wa	ater herein gran	ted is only a t	emporar
allo	wance and	d that the	final wa		ined under thi	s permit
MTTT			- 4.1	ater right obta		1
hene	pe dep ficial us	endent upo: se It is a	n the a	amount of wate	r actually pl	laced to
bene a re	ficial us	se. It is a	n the a also unde	amount of wate erstood that th	er actually pl is right must a	allow for
a re equi	ficial us asonable pped with	se. It is a lowering of latwo (2)	n the a also unde the sta inch ope	amount of wate erstood that the atic water level ening for measur	er actually plis right must a l. This well ing depth to wa	allow for shall be ater. I
a re equi the	ficial us asonable pped with well is	se. It is a lowering of a two (2) flowing, a	n the a also unde the sta inch ope valve	amount of wate erstood that the atic water level ening for measur must be instal	er actually plis right must a l. This well ing depth to wa led and maint	allow for shall be ater. It ained to
a re equi the prev	ficial us asonable pped with well is ent waste	se. It is a lowering of a two (2) flowing, a c. A totali	n the a also unde the sta inch ope valve zing met	amount of wate erstood that the atic water level ening for measur must be instal ter must be inst	er actually plis right must a l. This well ing depth to wa led and maint alled and maint	allow for shall be ater. I ained to tained in
a re equi the prev the meas	ficial us asonable pped with well is ent waste dischargurements	se. It is a lowering of a two (2) flowing, a e. A totali must be kep	n the a also unde the sta inch ope valve zing met near t	amount of wate erstood that the atic water level ening for measur must be instal	er actually plis right must a l. This well ing depth to wa led and maint alled and maint diversion and	allow for shall be ater. I ained to tained in accurate
a re equi the prev the meas	ficial us asonable pped with well is ent waste dischargurements	se. It is a lowering of a two (2) flowing, a e. A totali	n the a also unde the sta inch ope valve zing met near t	amount of wate erstood that the atic water level ening for measur must be instalter must be instalted point of of	er actually plis right must a l. This well ing depth to wa led and maint alled and maint diversion and	allow for shall be ater. It ained to tained in accurate
a re equi the prev the meas	ficial us asonable pped with well is ent waste dischargurements	se. It is a lowering of a two (2) flowing, a e. A totali must be kep	n the a also unde the sta inch ope valve zing met near t	amount of wate erstood that the atic water level ening for measur must be instalter must be instalted point of of	er actually plis right must a l. This well ing depth to wa led and maint alled and maint diversion and	allow for shall be ater. I ained to tained in accurate
a re equi the prev the meas	ficial us asonable pped with well is ent waste dischargurements	se. It is a lowering of a two (2) flowing, a e. A totali must be kep	n the a also unde the sta inch ope valve zing met near t	amount of wate erstood that the atic water level ening for measur must be instalter must be instalted point of of	er actually plis right must a l. This well ing depth to wa led and maint alled and maint diversion and	allow for shall be ater. I ained to tained in accurate
a re equi the prev the meas (CON	ficial us asonable pped with well is ent waste dischargurements	se. It is a lowering of a two (2) flowing, a e. A totali must be kep PAGE 2)	n the also under the state of war	amount of wate erstood that the atic water level ening for measur must be instalter must be instalted point of of	er actually plis right must al. This well ing depth to walled and maintalled and maintaliversion and eneficial use.	allow for shall be ater. I ained to ained in accurate The
a re equi the prev the meas (CON	ficial us asonable pped with well is ent waste discharg urements TINUED OF	se. It is a lowering of a two (2) flowing, a e. A totali e pipeline must be kep PAGE 2)	n the also under the state of war	amount of water erstood that the atic water level ening for measur must be instalter must be instalted point of other placed to be to the amount which can be to the amount which we amount which we amount which we amount which we amount w	er actually plis right must a l. This well ing depth to walled and maintalled and maintaliversion and eneficial use.	allow for shall be ater. I ained to accurate The
a re equi the prev the meas (CON	ficial us asonable pped with well is ent waste discharg urements TINUED ON	se. It is a lowering of a two (2) flowing, a e. A totaline must be kep I PAGE 2)	n the also under the state of war to the limited the state of the stat	amount of water erstood that the atic water level ening for measur must be instalter must be instalter must be instalter point of other placed to be to the amount which can be to feet per second	er actually plis right must a l. This well ing depth to walled and maintalled and maintaliversion and eneficial use.	allow for shall be ater. I ained to accurate The
a re equi the prev the meas (CON	ficial us asonable pped with well is ent waste discharg urements TINUED ON	se. It is a lowering of a two (2) flowing, a e. A totaline must be kep PAGE 2)	n the also under the state inch oper valve zing met near tot of war	amount of water erstood that the atic water level ening for measur must be instalter must be instalter must be instalter placed to be to the amount which can be to the amount which can be to the effect per second	er actually plis right must a l. This well ing depth to walled and maintalled and maintaliversion and eneficial use.	allow for shall be ater. I ained to accurate The
a re equi the prev the meas (CON  The amou exceed mill	ficial us asonable pped with well is ent waste discharg urements TINUED ON	se. It is a lowering of a two (2) flowing, a e. A totaline pipeline must be kept PAGE 2)	n the also under the state inch oper valve zing met near tot of war	amount of water erstood that the atic water level ening for measur must be instalter must be instalter must be instalter point of contemplaced to be determined to the amount which can	er actually plis right must a l. This well ing depth to wa led and maintalled and maintaliversion and eneficial use.  But not to exceed but not not to exceed but not not to exceed but not not not not not not not not not no	allow for shall be ater. I ained to accurate The
a re equi the prev the meas (CON  The amou exceed mill Work must	ficial us asonable pped with well is ent waste discharg urements TINUED ON  1.5 ion gallo st be prosecute	se. It is a lowering of a two (2) flowing, a e. A totaline pipeline must be kept PAGE 2) be appropriated shall be appropriated shall be work shall be filed by	n the also under the stainch open valve zing met near tot of water tot	amount of water erstood that the atic water level ening for measur must be instalter must be instalter must be instalter must be instalter point of other placed to be determined to the amount which can be determined to the	er actually plis right must a l. This well ing depth to wa led and maintalled and maintaliversion and eneficial use.  But not to exceed but not not to exceed but not not to exceed but not not not not not not not not not no	allow for shall be ater. I ained to accurate The  e, and not to ed 124.0
a re equi the prev the meas (CON  The amou exceed mill  Work mus Proof of c	ficial us asonable pped with well is ent waste discharg urements TINUED ON  1.5 ion gallo st be prosecute completion of vater to	se. It is a lowering of a two (2) flowing, a se. A totaline pipeline must be kept I PAGE 2)  be appropriated shall be appropriated shall be work shall be filed to beneficial use shall be shall	n the also under the state inch open valve zing met near to tof war to	amount of water erstood that the atic water level ening for measur must be instalter must be instalter must be instalter point of deter placed to be to the amount which can be deter provided to be determined by the completed on or before the before	r actually plis right must a l. This well ing depth to walled and maintalled and maintaliversion and eneficial use.  applied to beneficial use but not to exceed but not to exceed an January 7,  February 7,  January 7,	allow for shall be ater. I ained to accurate The  e, and not to ed 124.0  2000  2002
a re equi the prev the meas (CON  The amou exceed mill Work mus Proof of con Application	ficial us asonable pped with well is ent waste discharg urements TINUED ON  int of water to  ion gallo st be prosecute completion of water to he application	se. It is a lowering of a two (2) flowing, a e. A totaline pipeline must be kept PAGE 2)  be appropriated shall be appropriated shall be filed to beneficial use shall of water to beneficial	n the also under the stainch open valve zing met near tot of was stall be filed on or ial use shall be	amount of water erstood that the atic water level ening for measur must be instalter must be instalter must be instalter point of contemplaced to be determined to the amount which can	r actually plis right must a l. This well ing depth to walled and maintalled and maintaliversion and eneficial use.  Danuary 7,  February 7,  January 7,  February 7,	allow for shall be ater. I ained to ained in accurate The  e, and not to ed 124.0  2000  2002  2002
a re equi the prev the meas (CON  The amou exceed mill Work mus Proof of con Application	ficial us asonable pped with well is ent waste discharg urements TINUED ON  int of water to  ion gallo st be prosecute completion of water to he application	se. It is a lowering of a two (2) flowing, a e. A totaline pipeline must be kept PAGE 2)  be appropriated shall be appropriated shall be filed to beneficial use shall of water to beneficial	n the also under the stainch open valve zing met near tot of was stall be filed on or ial use shall be	amount of water erstood that the atic water level ening for measur must be instalter must be instalter must be instalter point of deter placed to be to the amount which can be deter provided to be determined by the completed on or before the before	r actually plis right must a l. This well ing depth to walled and maintalled and maintaliversion and eneficial use.  Danuary 7,  February 7,  January 7,  February 7,	allow for shall be ater. I ained to ained in accurate The  e, and not to ed 124.0  2000  2002  2002
a re equi the prev the meas (CON  The amou exceed mill Work mus Proof of con Application Proof of to Map in su	ficial us asonable pped with well is ent waste discharg urements TINUED OF	se. It is a lowering of a two (2) flowing, a e. A totaline pipeline must be kept PAGE 2)  be appropriated shall be appropriated shall be filed beneficial use shall of water to beneficial use shall be for the shall be filed beneficial use shall be	n the also under the state inch open walve zing met near to of war	amount of water erstood that the atic water level ening for measur must be instalter must be instalter must be instalter must be instalter placed to be ter placed to be ter placed to be ter placed on or before the filed on or bef	er actually place is right must at all. This well ing depth to walled and maintalled and maintalled and maintalled and eneficial use.  Exampled to beneficial use but not to exceed but not to exceed but not to exceed an and energy 7, February 7, F	allow for shall be ater. I ained to ained in accurate The  e, and not to ed 124.0  2000  2000  2002  2002
a re equi the prev the meas (CON  The amou exceed mill Work mus Proof of c Application  Proof of t Map in su  Completion	ficial us asonable pped with well is ent waste discharg urements TINUED ON  ion gallo st be prosecute completion of water to the application upport of proof	se. It is a lowering of a two (2) flowing, a se. A totaline pipeline must be kept PAGE 2)  be appropriated shall be appropriated shall be filed to beneficial use shall of water to beneficial use shall so beneficial use shall be filed to be filed	n the also under the stainch open valve zing met near to of was stated to the stated t	amount of water erstood that the atic water level ening for measur must be instalter must be instalter must be instalter point of contemplaced to be determined to the amount which can	er actually place is right must at all. This well ing depth to walled and maintalled and maintalled and maintalled and eneficial use.  Exampled to beneficial use but not to exceed but not not not not not not not not not no	allow for shall be ater. I ained to ained it accurate The  e, and not to ed 124.0  2000  2002  2002  J/A  NIPSEED, I
a re equi the prev the meas (CON  The amou exceed mill Work mus Proof of c Application  Completion	ficial us asonable pped with well is ent waste discharg urements TINUED ON  ion gallo st be prosecute completion of water to the application upport of proof	se. It is a lowering of a two (2) flowing, a e. A totaline pipeline must be kept PAGE 2)  be appropriated shall be appropriated shall be filed beneficial use shall of water to beneficial use shall be for the shall be filed beneficial use shall be	n the also under the stainch open valve zing met near to of was stated to the stated t	amount of water erstood that the atic water level ening for measur must be instalter must be instalter must be instalter must be instalter must be instalted to be the point of of the placed to be the placed to be the completed on or before the filed on	er actually plis right must and right must and led and maintalled and maintalled and maintalled and maintalled and use.  Exampled to beneficial use but not to exceed but not	allow for shall be ater. I ained to ained it accurate The  e, and not to ed 124.0  2000  2002  2002  J/A  NIPSEED, I
a re equi the prev the meas (CON  The amou exceed mill  Work mus Proof of c Application Proof of be	ficial us asonable pped with well is ent waste dischargurements TINUED Of the prosecute completion of water to the application apport of proof of work filed	se. It is a lowering of a two (2) flowing, a se. A totaline pipeline must be kept PAGE 2)  be appropriated shall be appropriated shall be filed to beneficial use shall of water to beneficial use shall so beneficial use shall be filed to be filed	n the also under the stainch open valve zing met near to of ward of ward of ward of ward of the filed on on the filed on the fi	amount of water erstood that the atic water level ening for measur must be installer placed to be ter placed to be ter placed to be ter placed on or before	er actually plis right must a l. This well ing depth to walled and maintalled and maintaliversion and eneficial use.  But not to exceed but not not to exceed but not not to exceed but not not to exceed but not not not not not not not not not no	allow for shall be ater. It ained to ained in accurate The  e, and not to ed 124.09  2000  2000  2002  1/A  NIPSEED, For the seal of my

totalizing meter must be installed before any use of water begins, or before the Proof of Completion of Work is filed. This source is located within an area designated by the State Engineer, pursuant to NRS 534.030. The State retains the right to regulate the use of the water herein granted at any and all times.

This permit does not extend the permittee the right of ingress and

egress on public, private or corporate lands.

The total combined duty of water under Permit 41141, Certificate 11784, and Permit 60072 shall not exceed 124.05 million gallons annually.

The issuance of this permit does not waive the requirements that the permit holder obtain other permits from State, Federal and local agencies.

A monthly report shall be submitted to the State Engineer within 10 days from the end of each month which shall include the amount of water pumped from the well and the amount of water used.